

HIN0500

SERIES

A Toyota Group Company



1625 | 1625 Long







Α	To	∕ota	Group	Com	pany
---	----	------	-------	-----	------

RANGE / SERIES	HINO 500					
MODEL NAME	1625	1625 Long				
MODEL CODE	FG8JJ7A	FG8JP7A				
DRIVE SYSTEM	4 x 2 (6W)					
GROSS VEHICLE WEIGHT (Kg)	16,000					
GROSS COMBINATION MASS (Kg)	N/A					
TRANSMISSION	6-Speed M/T with Overdrive					
TIRES & RIMS	11R22.5-16PR					
FUEL TANK CAPACITY (L)	200					
DIMENSIONS						
Wheelbase (mm)	4,330	5,530				
Length (mm)	7,785	9,485				
Width (mm)	2,490					
Height (mm)	2,750	2,745				
ENGINE						
Model	J08E-WF					
Emission Standard	Euro 4					
Max. Engine Speed (rpm)	2,600					
Туре	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 6-Cylinder, Overhead Camshaft, Water-cooled					
Combustion System	Direct Injection Type					
Fuel Injection System	Electronic Control Common Rail Type					
Displacement (L)	7.684					
PERFORMANCE						
Max. Output (PS) ISO Net JIS Gross	240 245					
Max. Torque (Nm) ISO Net JIS Gross	716 726					
Max. Speed (kph)	104					
SUSPENSION						
Front	Semi-elliptic Tapered Leaf Springs (Reinforced Type) with Double Acting Shock Absorbers and Stabilizer Bar	Semi-elliptic Tapered Leaf Springs (Reinforced Type) with Double Acting Shock Absorbers				
Rear	Semi-elliptic Main and Auxiliary Leaf Springs (Reinforced Type)					
BRAKES						
Service (Type)	Full Air, Dual-Circuit, "S" Cam Type, Equipped with ABS					
(Features)	Leading and Trailing Shoes for Front and Rear Wheels					
Parking	Air-operated Spring Brake Acting on Rear Axle					





