



HINO200

SERIES

A Toyota Group Company



415



THE ALL-NEW

200
SERIES



A Toyota Group Company

L I G H T & C O N V E N I E N T



Toyota 1GD-FTV



R451, 5-Speed Manual Transmission

PERFORMANCE

Equipped with tried and tested Toyota engine and transmission technology for unmatched reliability, fuel-efficiency and optimum power and torque

TOYOTA
GROUP
QUALITY

SAFETY

Puts priority on driver's safety through active and passive safety features



Tubeless Tires



Front Disc & Rear Drum Brake Configuration



Side Door Beam

SPECIFICATIONS

RANGE / SERIES	HINO 200
MODEL NAME	415
DRIVE SYSTEM	4 x 2 (4W)
ENGINE	
Model	1GD-FTV
Max. Output (PS) ISO Net	144
Max. Torque (Nm) ISO Net	300
Emission Standard	Euro 4
Max. Engine Speed (rpm)	4,400
Type	Diesel, Turbo-charged & Intercooled, 4-Cycle, Vertical, Inline, 4-Cylinder, Double Overhead Camshaft, Water-cooled
Combustion System	Compression Ignition, 4-Stroke
Fuel Injection System	Electronic Control Common Rail Type
Displacement (L)	2,755
Fuel Tank Capacity (L)	80
TRANSMISSION	
Type	R451, 5-Speed M/T with Overdrive
PERFORMANCE	
Max. Speed (kph)	130
Gradeability (%)	43.0
BRAKES	
Service (Type) (Features)	Dual-Circuit, Hydraulic, Vacuum Assist Front: Disc Brake, Rear: Drum Brake with Auto Brakeshoe Adjuster
Parking	Mechanical, Internal Expanding, Acting on Transmission Output Shaft
WHEELS & TIRES	
Rim Size	15 x 5J
Tire Size	195/75R15
SUSPENSIONS	
Front	Double Wishbone, Independent Torsion Bar Springs with Double Acting Shock Absorbers and Stabilizer Bar
Rear	Semi-Elliptic Main and Auxiliary Leaf Springs and Rubber Rebound Bumpers with Double Acting Shock Absorbers
SAFETY & OTHER AMENITIES	
Cab Airconditioning	Equipped
Power Door & Window	Equipped
Anti-lock Brake System (ABS) and Vehicle Stability Control (VSC)	Optional
SRS Airbag (Driver)	Optional
DIMENSIONS & WEIGHTS	
Wheelbase (mm)	2,545
Length (mm)	4,595
Width (mm)	1,695
Height (mm)	2,030
Gross Vehicle Weight (Kg)	3,800
Chassis Mass (Kg)	1,660

EASE OF USE


Equipped with a double wishbone front suspension, the Hino 200 Series provides a comfortable ride that minimizes fatigue even over extended periods of driving.

With a minimum turning radius of 4.7 meters, the vehicle is ideal for narrow streets and tight corners.

A lower bed design makes it easier to load and unload cargo.



Low Bed Height



Double Wishbone Front Suspension



4.7 meters Turning Radius

Small Turning Radius



www.hino.com.ph



/HinoMotorsPH



@HinoMotorsPH



hinomotors_philippines